




主要技术参数 (断路器用) MAIN TECHNICA DATA (FOR CIRCUIT BREAKER)

额定电压 Rated voltage	12KV
额定电流 Rated current	1250A
额定频率 Rated frequency	50/60HZ
额定短路开断电流 Rated short-circuit breaking current	31.5KA
额定短路开断电流开断次数 Operations of short-circuit breaking current interruption	30次
最大直流分量 Max.DC-component	50%
额定短路关合电流 Rated short-circuit making current	80KA
额定峰值耐受电流 Rated peak withstand current	80KA
额定短时耐受电流(4秒) Rated short-time withstand current(4s)	31.5KA
额定单个电容器组开断电流 Rated breaking current of single capacitor bank	#630A
额定背对背电容器开断电流 Rated breaking current of back to back capacitor bank	#400A
局部放电值 (1.1Ur) Partial discharge value(with a voltage of 1.1Ur applied)	≤1pc
短时(1min)工频耐受电压 Short-time(1min) power-frequency withstand voltage	49KV
雷电冲击耐受电压(峰值) Lightning impulse withstand voltage(peak)	85KV
额定触头压力下限时的回路电阻 Circuit resistance at minimum added force	≤18 μΩ
机械寿命 Mechanical life	30000次
触头自闭力 Closing force due to bellows and atmosphere	100 ± 30N
额定开距下的触头反力 Force required to hold contacts open at full stroke	200 ± 30N
触头允许磨损厚度 Contact erosion limit	3mm
贮存期 Shelf life	20年
质量 Total mass of embedded pole	12Kg
额定操作顺序 Rated operating sequence	O-0.3s-CO-180s-CO

配套真空开关的机械参数(建议值)MECHANICAL DATA OF SWITCH RECOMMENDATIONS WITH THE INTERRUPTERS

触头开距 Rated contact stroke	$9 \pm 1\text{mm}$
触头接触行程 Contact connection stroke	$4 \pm 1\text{mm}$
平均分闸速度（0–6mm行程） Average opening speed（0–6mm stroke）	$1.1 \pm 0.2\text{m/s}$
平均合闸速度（6mm–触头闭合） Average closing speed（6mm–contact making）	$0.6 \pm 0.2\text{m/s}$
触头初压力 Added external contact force at contact touch point	$\geq 2100\text{N}$
额定触头压力 Added force on closed contacts	$3100^{+600}_{-200}\text{N}$
触头合闸弹跳时间 Max.bouncing duration	$\leq 3\text{ms}$
触头分合闸不同期 Out of simultaneity of contact closing and opening	$\leq 2\text{ms}$
分闸触头反弹幅值 Max. rebound distance	$\leq 2\text{mm}$
分闸触头过冲幅值 Max. overtravel	$\leq 2\text{mm}$

备注 (Note) :
#订货时需与BOV公司协商(Must consult with BOV);